

PV-202 19mm/45m harmaa - Vesiletkukela ja suojakaappi



PV-202 19mm/45m harmaa - Vesiletkukela ja suojakaappi



Kastelukäyttöön tarkoitettu kaappi ja letkukela - yhdistelmä. Suunniteltu asennettavaksi sisätiloihin pinta-asenteisena tai upotettuna erikseen myytävän upotuskehyyksen avulla. These cabinets and reels are made of epoxy powder-coated steel sheeting, 1.25 mm thick for the fire hydrant cabinets and 1 mm thick for the hose reels. The reels are consistently painted red. Cabinets are available in three standard colors: white, grey, and red, with other colors available by special order. All cabinets feature a welded structural back wall and reinforced doors with adjustable steel hinges. The door is equipped with a special lock including a breakable lock protector. Doors open 180 degrees to allow free functioning of a hose reel installed on the door. The reel hubs are specially brass-molded and tested. Fire hydrant hoses comply with standard EN 694 and feature lightweight polyester weave reinforcement. The lightweight hoses operate at 1.2 MPa with a burst pressure of 9 MPa (+20C). Alternatively, fire hydrant cabinets can be equipped with a nitrile/PVC hose operating at 1.2 MPa with a burst pressure of 4 MPa (+20C). (Please refer to the product stats to confirm the assembled hose). While lightweight, the hose is not recommended for continuous use in cleaning heavily worn floor surfaces. A hose/nozzle holder prevents the hose from getting caught between the door. All cabinet models come with a spring-reinforced feed hose and include a direct/fog nozzle and 1 shut-off valve for fire hydrant cabinets

Ominaisuuudet

LVI-numero	2953388
EN 671-1 / 2012 hyväksytty	ei
Letkun tyyppi	kevytletku
Väri	Harmaa (RAL 7040)
Letkun pituus (m)	45
Letkun halkaisija	19mm (3/4")
Korkeus (mm)	990
Leveys (mm)	690
Syvyys (mm)	290